

Purlin & Rail Sections



ZETA

Fully effective section offering maximum efficiency.

No sag bars for majority of modern roofing applications.

Ideal purlin section for spans up to 7.60m.

Depths available:

125, 150, 175 and 200mm

SYSTEMS


SLEEVED

DOUBLE SPAN

HEAVY END BAY

DOUBLE SPAN HEB

BUTTED



ZETA II

'Zed' section with web stiffeners offering maximum structural efficiency for weight of material used.

Ideal for longer spans and heavier loadings.

Depths available:

225, 245, 265 and 285mm

SLEEVED

HEAVY END BAY

BUTTED



ZED

Plain Zed offering simple construction details.

Fully compatible range of CW sections for framing around openings.

For use as a purlin it is better suited for the shorter span and higher roof pitch.

Depths available:

125, 140, 155, 170, 185, 200, 240 and 300mm.

SLEEVED

HEAVY END BAY

BUTTED






Available Thickness (mm)

Zeta

Depth (mm)	1.3	1.4	1.5	1.6	1.7	1.8	2.0	2.5	3.0	3.2
125	✓	✓	✓		✓	✓	✓			
150	✓	✓	✓		✓	✓	✓	✓		
175	✓	✓	✓	✓	✓	✓	✓	✓		
200	✓	✓	✓	✓		✓	✓	✓		

Zeta II



225	✓	√	✓	✓	✓	✓		
245	✓	✓	✓	✓	✓	✓		
265		✓	✓	✓	✓	✓	✓	
285		✓	✓	✓	✓	✓	✓	

Zed



125	✓	✓	√	✓	✓			
140	✓	✓	✓	✓	✓			
155	✓	✓	✓	✓	✓			
170	√	✓	✓	✓	✓			
185	✓	✓	✓	✓	✓			
200	✓	✓	✓	✓	✓	✓		
240					✓	✓	✓	✓
300						√	√	✓

Contact Us: Ayrshire Metals Limited, Royal Oak Way, Daventry NN11 8NR Tel: +44 (0) 1327 300990 Email: sales@ayrshire.co.uk www.ayrshire.co.uk















